

# 800/1500 CFM Modular Ceiling Inlet

A new concept in controlling air speed and direction  
Consistent performance from 0 to 100% opening position



- Constructed of 100% polyethylene for long lasting durability. Can easily be washed down with high pressure without the risk of damage.
- Double wall thickness with a 1" air space offers maximum insulation value. Eliminates condensation during cold weather.
- Allow better control and precision of openings compared to continuous Baffle boards during cold weather.
- During cold weather air is directed upwards, efficiently warming the fresh air before it reaches animals. Prevents drafts.
- During hot weather air can be directed downward, uniformly distributing fresh air on to the animals for optimal comfort and cooling.
- Easy to install. Inlet does not protrud into the attic so it can be installed over a rafter if necessary. No compromise on inlet locations.
- Unique Insulation Stop connection to the Inlet for fast and secure installation.
- Possibility to hang a 3/4" nylon pulley in the eye bolt to prevent any premature wear of nylon cord that supports the lid.
- Exclusive 4-1/2" deep Inlet body keeps the winching hardware out of the airstream. Eliminates the common problem of icing during cold weather.

Also creates better mixing of incoming fresh air with warm air at the ceiling. And...it keeps the airstream away from water lines, electrical conduits, etc.

Authorized dealer

GSI GROUP



**GSI Electronics Inc.**

5200, Armand-Frappier, Saint-Hubert (Qc) Canada J3Z 1G5

Toll free : 1-877-926-2777 • Fax 450-926-2780

[www.gsi-electronics.com](http://www.gsi-electronics.com)